

StrongEdge

Water Clear Flowing Epoxy System

VOC Free

Now, Tenax has produced StrongEdge, the strongest clear, flowing epoxy specifically designed for fabrication and lamination. Once applied on a countertop, the stone or substrate will not delaminate or break where StrongEdge was applied! StrongEdge is the clearest flowing epoxy on the market. StrongEdge does not shrink, it takes a polish, as well as accepts colors to color match the stone if necessary.

With a 2:1 mix ratio and a set time of about 2 hours at 75 degrees, Tenax StrongEdge maintains the clearest epoxy with a cure time of 2 hours or less, without losing its structural integrity.

Now Available in
a Cartridge!

Cures in 2
Hours or less*



Water Clear



StrongEdge Advantage:

- The clearest epoxy on the market
- Extremely strong adhesion
- Glues stone to metal, wood, other substrates, anchor bolts, etc
- Easily accepts color
- High polish finish
- Working time of 25 minutes
- Cures in about 2 hours at 75 Degrees
- May be used indoor and outdoors
- Perfect to use with stone that will be put on a CNC, line machines or other automated equipment
- Indoor and outdoor use
- VOC Free

StrongEdge Applications:

- Laminating Granite, Marble, Engineered Stone, etc
- Repair of damaged stone
- Permanently secure Anchor bolts or sink brackets
- Fiberglass or metal rodding
- Where a VOC Free product must be used
- Gluing stone to stone, metal, wood, other substrates

Quart and Gallon Kits
Set of 3 includes:
2 part A, 1 part B

TENAX USA
www.tenaxusa.com
info@tenaxusa.com
1-800-341-0432

Download a free QR
Scanner and watch the
Strongedge video with
your smart phone

